



"WET LOOK WB" SEALER

FOR CONCRETE, MASONRY & NATURAL STONE

Formulated specifically to protect and give a "Wet Look" appearance to Concrete, Flagstone, Brick, Slate, Exposed Aggregate, Pavers, and other Porous Tile & Masonry Surfaces.

PRODUCT DESCRIPTION

Glaze 'N Seal "Wet Look WB" is an environmentally superior low VOC water-based sealer. It is especially formulated to give the surface that deepened, "Wet Look" appearance. It may be used indoors or outdoors and is extremely easy to apply and maintain. "Wet Look" WB is a quick drying, non-yellowing formula that protects against organic stains, including cooking oil and grease.

USES

"Wet Look WB" protects and beautifies all concrete and decorative concrete surfaces, exposed aggregate, pavers, natural stone and porous tile. It is ideal for driveways, patios and interior floors. For interior application, use **Glaze 'N Seal Acrylic Floor Polish** for an added durable abrasion resistance to foot traffic and to extend the life of the sealer.

FEATURES

- Deepened "Wet Look" appearance
- Easy to apply
- Meets all VOC regulations
- Never yellows
- Repels oil and grease stains
- Eligible for LEED points
- Non-flammable
- Blush resistant
- Breathable. Cleans up with water
- Re-coatable

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paint or sealer. If acid has been used, neutralize surface with a product like **Glaze 'N Seal Neutralizing Rinse** and allow surface to dry thoroughly before applying sealer. When water is used or surface is wet from rain, allow surface to dry 72-hours before sealing.

APPLICATION

Important Note: Always Test a small area of the surface to be sealed to verify penetration and satisfaction of sealed appearance.

Do not shake container. Apply two or more coats of sealer (*do not allow it to puddle*). Make sure each coat is dry to the touch before applying second coat; usually one to three hours. Allow additional drying time in moist climates. Sealer can be applied with brush, lamb's wool applicator or spray equipment, dependent on the porosity and texture of the surface. Apply between 55° and 80°F. Allow 72-hours curing time against heavy moisture and bulk water. Do not allow to freeze and avoid heavy usage for up to 72-hours. Sealer will continue to gain strength for up to one week.

SPECIFICATIONS

Base	Aqueous Acrylic Copolymer
Tukon Hardness	+6.0
Friction Level	Excess 6.3
Glass Transition Point	34°C
Density	8.58 lbs. per gallon
Refractive Index	Approx. 1.4077
Solids	Excess 16%
Appearance	Milky White — Dries Clear
VOC	Less than 100 grams per liter

Coverage: 100-400 sq. ft. per gallon dependent on porosity of the surface.

Maintenance: Sweep and mop floor regularly. For added abrasion and wear protection and to extend the life of the sealer on interior floors, use **Glaze 'N Seal Floor Polish** (*high-gloss or matte*) as a traffic coat.

Packaging: Glaze 'N Seal "Wet Look" WB Sealer is packaged in quarts, gallons, 5-gallon pails and 55-gallon drums.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • 800/486-1414
www.glaze-n-seal.com

FS 12-1/14